



From range:

BAAKUNITY

Article 5212 OPTIMUS Stone
Half shoe S1P SRC ESD



Certified for
orthopedic insoles
Details on www.baak.de/en



Relieve your
musculoskeletal system

Very foot conform
fitting & function

Upper

Stretchable and breathable Baak® Flex-Mesh, which adjusts to the foot like a sock, incl. stabilisation straps = Baak® **multi-widths** system, robust Baak® Rubber Skin enhancement, softly padded edge

Lining: climate regulating, stretchable textile lining
Tongue: stretchable closed sock construction, padded
Lacing: round laces, black/grey
Closing parts: combination of metal and plastic lacing elements

Insock

Soft damping Baak ESD orthostep footbed, breathable with a very high humidity absorption, antibacterial, fungicide, incl. size check (article 4663)

Sole

EVA/nitrile sole with **flex zone** in the ball section
EVA midsole with high energy absorption, damping impact for joints, knees and spine due to its full surface damping; nitrile outsole: robust, slip resistant (SRC), non-marking

Toecap

Light aluminium **flex cap**

Anti-penetration

Flexible, non-metallic anti-penetration insole board

Plus

Baak® **go&relax** system for a natural foot bending
Baak® **multi-widths** system
Baak® **fitting system** for an individual adjustment of different heights of foot arches

Sizes/Width

38 – 48 / Width range 10-14 in one shoe


BAAK® go&relax system



natural bending line



flex zone in ball area



foot fitting instead of straight

To the Unity Flyer



BAAK® multi-widths system



stretchable Baak® Flex-Mesh

The BAAK® Unity adjusts automatically to wider or slimmer feet.

BAAK® fitting system



fitting elements

The BAAK® Unity closes individually the gap between foot and safety shoe.

To the movie



Oskar explains the Baak®go&relax system



From range:

BAAKUNITY

Article 5212 OPTIMUS Stone
Half shoe S1P SRC ESD 



Certified for
orthopedic insoles
Details on www.baak.de/en



*Relieve your
musculoskeletal system*

*Very foot conform
fitting & function*

Weight	Approx. 560 g / piece (size 42)
Designation	According to EN ISO 20345 S1 SRC ESD
Examples for use	Areas without wetness impact, such as: Handicraft, automotive sector, electricity and energy sector, printing industry, disposal industry, packaging industry, logistics, aviation sector, administration